



Air Conditioner





Indoor Unit

L 05 S1 - L 24 S1

Outdoot Unit

LO 05 S1 - LO 24 S1

Products Line Up

Standard Split Wall

Standard Specifications

Indoor Unit Model Name	L 05 S1	L 09 S1	L 12 S1	L 18 S1	L 24 S1
Outdoor Unit Model Name	LO 05 S1	LO 09 S1	LO 12 S1	LO 18 S1	LO 24 S1
Capacity (PK)	0.5	1	1.5	2	2.5
Cooling Capacity (BTU/H)	5000	9000	12000	17000	24000
Power Consumption (W)	405	790	1066	1510	2348
Running Current (A)	1.8	3.7	5.3	7.9	11.8
Eer Cooling	12.4	10.5	10.6	10.7	10
Power Supply (V/Ph/Hz)	170-240V/1/50 Hz	175-240V/1/50 Hz	200-240V/1/50 Hz	200-240V/1/50 Hz	200-240V/1/50 Hz
Refrigerant	R410A	R410A	R410A	R410A	R410A
Air Flow Volume (m3/h)	430	470	500	800	1050

Indoor Unit


Dimensions (mm)	698 x 255 x 190	770 x 250 x 205	770 x 250 x 205	910 x 292 x 205	1010 x 315 x 220
Packing Dimensions (mm)	762 x 550 x 300	848 x 315 x 275	848 x 315 x 275	977 x 367 x 276	1094 x 386 x 300
Net Weight (Kg)	6.8	8	8	10	13
Noise Level (dB(A))	29	36	36	42	46

Outdoor Unit

Dimensions (mm)	600 x 500 x 232	600 x 500 x 232	700 x 552 x 256	780 x 605 x 290	902 x 650 x 307
Packing Dimensions (mm)	705 x 550 x 300	705 x 550 x 300	803 x 600 x 325	883 x 653 x 412	1028 x 705 x 430
Net Weight (Kg)	20	22	27	36	52
Noise Level (dB(A))	50	50	52	58	60

Pipe Size

Gas (Inch)	3/8"	3/8"	1/2"	1/2"	5/8"
Liquid (Inch)	1/4"	1/4"	1/4"	1/4"	1/4"



Indoor Unit

X 05 D1 - X 18 S1

Outdoot Unit

XO 05 D1 - XO 10 S1

Products Line Up

Deluxe Split Wall

Deluxe Specifications

Indoor Unit Model Name	X 05 D1	X 09 D1	X 12 S1	X 18 S1
Outdoor Unit Model Name	XO 05 D1	XO 09 D1	XO 12 S1	XO 18 S1
Capacity (PK)	0.5	1	1.5	2
Cooling Capacity (BTU/H)	5000	9000	12900	18000
Power Consumption (W)	359	739	1050	1480
Running Current (A)	1.6	3.1	4.7	7
Eer Cooling	10.9	11	11.6	11.7
Power Supply (V/Ph/Hz)	170-240V/1/50 Hz	170-240V/1/50 Hz	170-240V/1/50 Hz	170-240V/1/50 Hz
Refrigerant	R410A	R410A	R410A	R410A
Air Flow Volume (m3/h)	460	650	630	880

Indoor Unit

Dimensions (mm)	690 x 283 x 199	850 x 300 x 197	850 x 300 x 197	900 x 310 x 225
Packing Dimensions (mm)	760 x 347 x 277	900 x 370 x 270	900 x 370 x 270	950 x 380 x 290
Net Weight (Kg)	7	9	9.5	11
Noise Level (dB(A))	29	36	36	42

Outdoor Unit

Dimensions (mm)	665 x 420 x 280	660 x 500 x 240	720 x 540 x 260	802 x 535 x 298
Packing Dimensions (mm)	760 x 480 x 345	780 x 570 x 345	835 x 350 x 600	920 x 400 x 620
Net Weight (Kg)	18	24	27	36
Noise Level (dB(A))	49	49	49	52

Pipe Size

Gas (Inch)	3/8"	3/8"	1/2"	1/2"
Liquid (Inch)	1/4"	1/4"	1/4"	1/4"

Deluxe Units



Products Line Up

Standard Floor Stand

Standard Specifications

Indoor Unit Model Name	FS 71 L1	FS 125 L1
Outdoor Unit Model Name	FSO 71 L1	FSO 125 L1
Capacity (PK)	3	6
Cooling Capacity (BTU/H)	22000	48000
Power Consumption (W)	2345	4800
Running Current (A)	11.2	8.1
Eer Cooling	2.7	2.9
Power Supply (V/Ph/Hz)	220-240V/1/50Hz	380V/3/50Hz
Refrigerant	R410A	R410A
Air Flow Volume (m3/h)	900	1700

Indoor Unit

Dimensions (mm)	1740 x 480 x 330	1775 x 540 x 415
Packing Dimensions (mm)	1870 x 616 x 452	1893 x 632 x 535
Net Weight (Kg)	37	51
Noise Level (dB(A))	45	48

Outdoor Unit

Dimensions (mm)	902 x 307 x 650	1225 x 950 x 410
Packing Dimensions (mm)	1028 x 430 x 705	1380 x 1030 x 440
Net Weight (Kg)	47	100
Noise Level (dB(A))	60	60

Pipe Size

Gas (Inch)	5/8"	3/4"
Liquid (Inch)	3/8"	1/2"

Benefit

Of using Sansui Product.



Sssttt... it's very quiet

Kenyamanan super ekstra hanya untuk anda dengan tingkat kebisingan yang minim



Left or Right Drainage

Ruangan yang terbatas ? Jangan khawatir, kamu dapat memilih jalur pembuangan baik dari sisi kiri maupun kanan



Smart Airflow

Hembusan udara dengan fokus pada titik-titik panas agar ruangan lebih cepat dingin dan juga sejuk



Fireproof Protection

Produk Sansui™ juga dilengkapi dengan keamanan ekstra untuk masalah kelistrikan yang dapat menyebabkan kebakaran



Indoor Unit

FS 71 X1

Outdoot Unit

FSO 71 X1

Indoor Unit

FS 125 X1

Outdoot Unit

FSO 125 X1

Products Line Up

Deluxe Floor Stand

Deluxe Specifications

Indoor Unit Model Name	FS 71 X1	FS 125 X1
Outdoor Unit Model Name	FSO 71 X1	FSO 125 X1
Capacity (PK)	3	5
Cooling Capacity (BTU/H)	24000	42000
Power Consumption (W)	2200	4500
Running Current (A)	11	8
Eer Cooling	2.8	2.4
Power Supply (V/Ph/Hz)	220-240V/1/50 Hz	380-415V/3N/50 Hz
Refrigerant	R410A	R410A
Air Flow Volume (m3/h)	1200	1900

Indoor Unit

Dimensions (mm)	506 x 1780 x 315	580 x 1925 x 400
Packing Dimensions (mm)	620 x 1970 x 460	690 x 2100 x 565
Net Weight (Kg)	39	54
Noise Level (dB(A))	48	57

Outdoor Unit

Dimensions (mm)	825 x 655 x 310	940 x 1320 x 340
Packing Dimensions (mm)	945 x 725 x 435	1080 x 1440 x 430
Net Weight (Kg)	44	89
Noise Level (dB(A))	57	61

Pipe Size

Gas (Inch)	5/8"	3/8"
Liquid (Inch)	1/4"	3/4"

Floor Stand Units



Indoor Unit

X 09 P1-X 12 P1

Products Line Up

Portable


Specifications

Unit Name	X 09 P1	X 12 P1
Capacity (PK)	1	1.5
Cooling Capacity (BTU/H)	9000	12000
Power Consumption (W)	1030	1370
Running Current (A)	4.5	5.9
Eer Cooling	2.4	2.4
Power Supply (V/Ph/Hz)	220-240 ^v /1/50 ^{Hz}	220-240 ^v /1/50 ^{Hz}
Refrigerant	R410A	R410A
Air Flow Volume (m3/h)	410	410

Unit

Dimensions (mm)	475 x 798 x 417	475 x 798 x 417
Packing Dimensions (mm)	520 x 885 x 450	520 x 885 x 450
Net Weight (Kg)	30	30
Noise Level (dB(A))	50	50

Dealers:



Contact us

Interested? Call us now!

After Sales Service

Jl. Daan Mogot KM. 10, Ruko Green Mansion blok B 9-10,
Pesing, Kel. Kedaung Kaliangke, Kec.Cengkareng
Jakarta Barat

Tel. +62 811-9227-656

Email. ass@sbsarana.com

Scan

**Directly using the
navigation application**



Portable Unit